

**AUTOMOTIVE P.V.C. CABLE**

PART NO.	SIZE	CONDUCTOR CONSTRUCTION	INSULATION (PVC)		LENGTH
	MM.		MIN O.D.	MAX O.D.	METER
<b>CB-0.5</b>	0.50	MM.0.18 x 20	2.20	2.40	30M.
<b>CB-0.75</b>	0.75	MM.0.18 x 30	2.40	2.60	30M.
<b>CB-1</b>	1.0	MM.0.18 x 40	2.60	2.80	30M.
<b>CB-1.5</b>	1.5	MM.0.32 x 18	2.80	3.00	30M.
<b>CB-2</b>	2.0	MM.0.32 x 24	3.10	3.40	30M.
<b>CB-2.5</b>	2.5	MM.0.18 x 100	3.40	3.80	30M.
<b>CB-3</b>	3.0	MM.0.32 x 38	3.80	4.10	30M.
<b>CB-4</b>	4.0	MM.0.32 x 49	4.50	4.50	30M.
<b>CB-6</b>	6.0	MM.0.32 x 73	5.40	5.40	30M.

**P.V.C. BATTERY STARTER CABLE**

PART NO.	SIZE	CONDUCTOR CONSTRUCTION	INSULATION (PVC)		LENGTH
	MM.		MIN O.D.	MAX O.D.	METER
<b>BAT-25</b>	25	MM.0.32 x 35 x 7	11.1	11.5	100 M
<b>BAT-35</b>	35	MM.0.32 x 60 x 7	13.0	13	100 M
<b>BAT-50</b>	50	MM.0.32 x 31 x 19	15.0	15.0	100 M

**HALOGEN HEAD LAMP**

PART NO.	APPLICATION	VOLT	VEHICLE APPLICATION
<b>HH-101</b>	FOR TWO - LAMP SYSTEM	12 V.	ALL VEHICLE
<b>HH-102</b>	FOR FOUR - LAMP SYSTEM	12 V.	ALL VEHICLE
<b>HH-103</b>	FOR TWO - LAMP SYSTEM	12 V.	TOYOTA
<b>HH-104</b>	SPOTLIGHT	12V. - 24V.	ALL VEHICLE
<b>HH-105</b>	SPOTLIGHT	12 V.	D4D 4WD
<b>HH-106</b>	SPOTLIGHT	12 V.	D-MAX
<b>HH-107</b>	SPOTLIGHT	12 V.	D4D 2WD
<b>HH-108</b>	SPOTLIGHT	12 V.	D4D VIGO



# Automotive wire

Thai industrial standard ( TIS 118 - 2522)

Part number	Nominal cross sectional area mm.	Number and diameter of wire No/mm.	Approx conductor diameter mm.	Mean value of insulator thickness mm.	Approx overall diameter mm.	Max. conductor resistance at 20 C /Km	Max continuous current rating in free air (Ampere)	Package quantity in meter		
CB-0.5	0.5	16/0.20	1.0	0.6	2.2	37.1	8	30	500	
CB-0.75	0.75	24/0.20	1.2	0.6	2.4	24.7	11	30	500	
CB-1	1.0	32/0.20	1.4	0.6	2.6	18.5	13	30	500	
CB-1.5	1.5	30/0.25	1.6	0.6	2.8	12.7	16	30	500	
CB-2	2.0	28/0.30	1.9	0.6	3.1	9.42	20	30	500	
CB-2.5	2.5	50/0.25	2.1	0.7	3.5	7.60	23	30	500	
CB-3	3	44/0.30	2.3	0.7	3.7	6	26	30	500	
CB-4	4	56/0.30	2.6	0.8	4.2	4.71	31	30	500	
CB-6	6	84/0.30	3.2	0.9	5.0	3.14	40	30	500	
BAT-20	20	32/13 x 19						20	50	100
BAT-25	25	32/35 x 7						20	50	100
BAT-35	35	32/60 x 7						20	50	100
BAT-50	50	32/31 x 19						20	50	100
AVSS0.85	0.85							500		
AVSS1.25	1.25							500		

CB



BAT



AVSS

