

Brake Fluid Greena 500 – DOT 4



BRAKE 500 is high-quality brake oil, comprising polyethylene glycol ether mixed with additives. Its boiling point is more than 500 °F (260 °C) so it can withstand high temperatures and heavy loads. It has an appropriate viscosity for quality lubrication of pumps and other systems. It does not damage couplings or metal equipment in the brake system and clutch.

APPLICATIONS

Uses in either drum or disk brake systems of every kind of high efficiency vehicle, such as sedans, trucks, buses, tow trucks, tractors, etc., including oil clutch systems.

MEET REQUIREMENTS

- FMVSS 116 Grade DOT 3 and DOT 4
- SAE J-1703
- TISI 591-2528

TYPICAL INSPECTION

PROPERTIES	BRAKE 500
Color, ASTM	Report
Eq. Reflux Boiling Point, °C	255 Min
Wet Boiling Point, °C	165 Min
pH	7.0-11.5
Density, g/cm ³	1.010-1.055
Viscosity @ 100 °C, cSt.	1.5 Min

Packages: 200 litres, 1 litre and 0.5 litre

Brake Fluid - DOT 3



BRAKE DOT 3 is a brake fluid for use in all type of brake and hydraulic clutch system. The boiling point is above 400 oF. The features are :

- Increased safety through minimized drop in boiling point
- Will not damage the rubber components and corrode the metal parts in the brake system
- Fully compatible and miscible with other brake fluids of similar specification

APPLICATION

- BRAKE DOT 3 is suitable for passenger car, truck, bus and motorcycles

MEET REQUIREMENT

- FMVSS 116 Grade DOT 3
- SAE J-1703

TYPICAL INSPECTION

PROPERTIES	BRAKE DOT 3
Color, ASTM	L.1.0
Eq. Reflux Boiling Point, °C	205 Min
Wet Boiling Point, °C	140 Min
pH	7.00-11.5
Density, g/cm ³	1.010-1.055
Viscosity @ 100 °C, cSt.	1.5 Min

Package : 200 Litres