

RUST PROOF



RUST PROOF is a quality rust preventive oil. The product is oil film will typically provide corrosion protection on ferrous metal. Rust Proof is oily film, indoors protection can be used in-plant rust protection, In-process inventory. This product is provided de-watering property.

Usage of RUST PROOF

Rust Proof 0314, 1264, 528 : Oil type appropriate for oil film work.

Rust Proof W931, 532 : Solvent type appropriate for drying fast work.

Rust Proof 533 : Solvent type appropriate for thin film work. Safety because flash point higher than Rust Proof 532

Rust Proof is used for general proposes rust preventive oil. Parts can be dipped into a Rust Proof, can be sprayed or painted oil on parts.

Special characteristics of RUST PROOF

PROPERTIES	RUST PROOF					
	0314	W931	1264	528	532	533
Type	Oil	Oil	Oil	Oil	Wax	Wax
VISCOSITY @ 40 °c, cst.	4 Max	3 Max	4 Max	12 Max	3 Max	3 Max
FLASH POINT, °c	35 Min	35 Min	35 Min	180 Min	40 Min	75 Min
Appearance	Clear	Clear	Clear	Clear	Clear	Clear
Protection time, indoors (months)	3	9	12	12	12	12
Protection time, outdoors (months)	1	3	6	9	9	9

PACKAGING; 200 LITRES